



dexos 1™ LONG LIFE SYNTHETIC 5W-30

(2nd Generation) SN – ILSAC GF5

PART NUMBER:

1 Litre 19350776
5 Litre 19350777
20 Litre 19350778
205 Litre 19350779

PREMIUM SYNTHETIC MOTOR OIL FOR PETROL ENGINES

DESCRIPTION:

dexos 1™ is an innovation in engine oil. It was developed by GM for late model GM vehicles with petrol engines. It is also suitable for use in a wide variety of other makes and models. This 2nd generation dexos 1™ specification was created to provide better vehicle performance as well as low speed pre-ignition (LSPI) protection, particularly for small displacement turbo-charged engines. This new spec. is reflective of the global market shift towards higher performance lubricants and fuel economy in passenger cars. Setting stricter limits than some common industry standards, dexos 1™ demands fuel economy gains without sacrificing performance and durability.

ADVANTAGES:

- Excellent wear protection even under high permanent load with maximum power output.
- Applicable in gasoline engines.
- Low oil consumption due to minimum evaporative loss.
- Resists oxidation and thermal breakdown even in severe service.
- Protection against sludge and deposits.
- Maintains viscosity grade.

APPROVALS:

- GM dexos 1™ 2nd Generation (Approval # D10428HH075)

SPECIFICATIONS: (Meets or exceeds)

- SAE 5W30
- API SN
- ILSAC – GF 5

SUITABLE FOR USE WITH FOLLOWING SPECIFICATIONS:

- FORD M2C929-A FORD M2C946-A
- Chrysler MS 6395 Fiat 9.55535-CR1

BENEFITS:

ACDelco dexos 1™ SAE 5W-30 fulfils engine oil requirements for vehicles requiring dexos 1™, API SN and ILSAC GF-5. It assists in preventing deposits in the engine and turbocharger to ensure full boost pressure, engine power and fuel economy are maintained. Suitable for most high performance petrol and engines in passenger cars where a low viscosity oil is required, especially when equipped with exhaust catalysts systems.

TYPICAL CHARACTERISTICS:

Specific gravity @15° C kg/L	0.85
Viscosity at 40°C ASTM D 445 cSt	61.2
Viscosity at 100° C ASTM D 445 cSt	10.4
Viscosity index ASTM D 2270	160

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.

November 2017